

Product leaflet

| Product | Model No. | Ordering No. |
|---|-----------|--------------|
| Neck & chest protection, welding, Proban | SR 585-1 | T06-8011 |
| Neck & chest protection, welding, leather | SR 585-2 | T06-0808 |
| Face seal, welding, Proban | - | T06-8012 |
| Face seal, welding, leather | - | T06-0809 |
| Hose protection, Proban | SR 59021 | T06-4016 |

Product Description

The Neck & chest protection together with face seal gives the user a good protection against spatter and sparks when welding and grinding.

Suitable to use together with SR 580/SR 584 and/or SR 580 with gold-plated shield SR 587 and 2/3 visor SR 588-1 or SR 588-2.

The hose protection will prolong the life-time of the hose in these work situations.


The Proban material can be washed after use. Contact Sundström for further information.

Technical Specification

| | T06-8011 | T06-8012 | T06-0808 | T06-0809 | T06-4016 |
|----------------------------|---|--------------------|--|--------------------|--|
| Material | Proban | | Leather | | Proban |
| Weight | ≈ 5.5 oz (155 g) | ≈ 2.1 oz (60 g) | ≈ 12.3 oz (350 g) | ≈ 3.2 oz (90 g) | ≈ 2.6 oz (75 g) |
| Service temperature | -14 to 131 °F (-10 to +55 °C), < 90 % RH | | 14 to 131 °F (-10 to +55 °C), < 90 % RH | | 14 to 131 °F (-10 to +55 °C), < 90 % RH |
| Storage temperature | 4 to 104 °F (-20 to +40 °C), < 90 % RH | | 4 to 104 °F (-20 to +40 °C), < 90 % RH | | 4 to 104 °F (-20 to +40 °C), < 90 % RH |



T06-0811
T06-0808



T06-0812
T06-0809



T06-4016

Sundstrom Safety Inc.

143 Maple St.
Warwick, RI 02888

Office: 1-401-434-7300
Toll Free: 1-877-SUNDSTROM
Fax: 1-401-434-8300

info@srsafety.com
www.srsafety.com